



Geluidreducerende onderlaag



Acoustic Sublayer




Trittschall reduzierender Unterlage

**Rol / Roll**

**15** m<sup>2</sup>

- Breedte/Width 100 cm
- Lengte/Length 15 m
- Dikte/Thickness 4 mm



### Contactgeluid (IS)


#### Impact sound reduction

10 dB  $\Delta L_{lin}$  / 22 dB  $\Delta L_w$

(combined with Redupanel® and 6 and 9 mm wooden strip parquet and in combination with Jumpax® Nature and 11 mm prefab wooden strip flooring)

10 dB  $\Delta L_{lin}$  / 23 dB  $\Delta L_w$

(combined with Redupanel® and 20 mm 2 layer engineered wood plank)




### Thermische weerstand (R-waarde)

#### Thermal resistance

0,12 m<sup>2</sup>. K/W


TOG 1,2



### Warmtegeleidingscoëfficiënt (TC)

#### Thermal conductivity

0,0384 W/m.K



### Brandklasse NEN-EN-13501-1

#### Fire classification

F<sub>fl-s1</sub>



**Toepassing:**

- Contactgeluid reducerende onderlaag in combinatie met Redupanel® en 6 en 9 mm massief parket en 2 laags lamelplank, en in combinatie met Jumpax® Nature en 11 mm prefab tapis. Cocofloor® is ook toe te passen in combinatie met Jumpax® CP.

**Leginstructie:**

Altijd een PE-folie van 150 µm aanbrengen, de naden 20 cm overlappen en afplakken met Unifloor ALU-tape (voorzien van rubber lijmlaag). Rol de banen naast elkaar uit. Leg de Cocofloor® in dezelfde richting als de Redupanel® delen.

Kijk op [www.unifloor.nl](http://www.unifloor.nl) voor de meest actuele informatie.

**Application:**

- A decoupling acoustic sublayer for ReduPanel®, for fixing 6 and 9 mm solid wood strip flooring and 2 layer engineered wood plank onto, and in combination with Jumpax® Nature and prefab wooden strip flooring. Cocofloor® can also be used in combination with Jumpax® CP.

**Fitting instructions:**

Always apply a 150 micron polyethylene film over the entire surface. Overlap seams with 20 cm and tape them off over their entire lengths with Unifloor ALU tape (with latex glue). Now roll out CocoFloor® in the same length direction as ReduPanel®.

Please check [www.unifloor.nl/en](http://www.unifloor.nl/en) for the most up-to-date information.

**Anwendung:**

- Trittschall reduzierender Unterlage in Kombination mit Redupanel® und Jumpax® CP.

**Verlege-Anleitung:**

Immer eine PE-Folie von 150 µm verwenden, die Nähte 20 cm überlappen lassen und mit Unifloor Aluminiumband verkleben.

Für die neusten Information: [www.unifloor.info](http://www.unifloor.info).